

VINTAGE

WOOD - PRODUCT DATASHEET 2020



TECHNICAL DATA (EN 13489)		
Reaction to fire	EN 14342 Table 1	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Taber Abraser/Lacquer's wear resistance Protoco Hardwax Oil	EN 13696	N/A
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	20
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,11
Construction	3-layer with softwood core	

Hansskog 2020.05

INSTALLATION	
Installation method	2-lock for floating or glue down
Installation instruction	Download from www.tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²	

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting, Transition moulding, Pipe covers
Care & Maintenance	Wood Floor Care Kit / Spray Mop Kit Bioclean Hardwax Oil Refresher Hardwax Oil
See more alternatives and the complete range of accessories @ www.tarkett.com	

MAINTENANCE
These Tarkett wooden floors have a Protoco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com

Vintage Protoco Hardwax Oil

98 %
98 %
Natural
Renewable

100 %
Recyclable



2-LOCK



www.realwood.eu

VINTAGE

WOOD - PRODUCT DATASHEET 2020

DESIGN

Oak planks that witness the passage of time. Each board is crafted with details like saw marks and indentations so it appears worn from day one, yet remains highly resistant over time. Vintage planks are designed with a minibevel along the length and they are particularly suitable for public areas thanks to a special camouflage effect and a hardwax oil finish.

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side)	Character	Colour	Latin name	DoP no.	Wear layer thk (mm)	Board/ pack	m2/ pack	m2/ pallet	Net weight/ m2 (kg)
Vintage Oak Copenhagen	7877040	2 000 x 190 x 14	1-strip	Proteco Hardwax Oil	Partial saw marks, brushed	Handmade minibevel	Calm	Warm grey	1	0190-0105	3,5	6	2,28	79,80	7,9
Vintage Oak Uppsala	7876105	2 000 x 162 x 14	1-strip	Proteco Hardwax Oil	Partial saw marks, brushed	Handmade minibevel	Lively	White	1	0190-0105	3,5	6	1,94	69,84	7,9
Vintage Oak Lund	7877043	2 000 x 190 x 14	1-strip	Proteco Hardwax Oil	Partial saw marks, brushed	Handmade minibevel	Calm	Warm grey	1	0190-0105	3,5	6	2,28	79,80	7,9
Vintage Oak Orléans	7876104	2 000 x 162 x 14	1-strip	Proteco Hardwax Oil	Full saw marks, brushed	Handmade minibevel	Lively	Warm grey	1	0190-0105	3,5	6	1,94	69,84	7,9
Vintage Oak Montpellier	7877041	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Partial saw marks, brushed	Handmade minibevel	Calm	Warm beige	1	0190-0105	3,5	6	2,51	87,85	7,9
Vintage Oak Chester	7877042	2 200 x 190 x 14	1-strip	Proteco Hardwax Oil	Indentation marks, brushed	Handmade minibevel	Lively	Warm brown	1	0190-0105	3,5	6	2,51	87,85	7,9
Vintage Oak Salamanca	7877044	2 000 x 190 x 14	1-strip	Proteco Hardwax Oil	Partial saw marks, brushed	Handmade minibevel	Lively	Warm brown	1	0190-0105	3,5	6	2,28	79,80	7,9

Due to the nature of the material this table shows typical values.

1: Fraxinus Angustifolia, 2: Quercus Robur & Quercus Petraea



Vintage Oak Copenhagen



Vintage Oak Uppsala



Vintage Oak Lund



Vintage Oak Orléans



Vintage Oak Montpellier



Vintage Oak Chester



Vintage Oak Salamanca

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com.

Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com